



	HyQube 350	HyQube 500	HyQube 700
<b>Dimensions</b>	1.8 x 1.8 x 1.8 m	2.2 x 2.2 x 2.2 m	2.2 x 2.2 x 2.2 m
<b>Interface</b>	Automatic fill using touch screen interface		
<b>Hydrogen Compressor</b>	Fully integrated		
<b>Electrical Requirement</b>	32A three-phase	63A three-phase	63A three-phase
<b>Hydrogen Inputs</b>	3	2	2
<b>Storage Connections</b>	0	1	1
<b>Minimum / Maximum Input</b>	90 bar* / 350 bar	35 bar / 500 bar	35 bar / 500 bar
<b>Filling Protocols</b>	FCSL Direct Boost	FCSL Direct boost J2601/2010 CEP/TME	FCSL Direct boost FCSL based on J2601 CEP/TME
<b>Filling Nozzle Options</b>	350 bar	350 bar 700 bar 700 bar with IR	700 bar with IR
<b>Mass Flow Meter</b>	No	Optional	Optional
<b>External Storage</b>	No	Optional 600l 500bar	On Request
<b>Certification</b>	CE, UKCA		

[www.fuelcellsystems.co.uk](http://www.fuelcellsystems.co.uk)

\* 90 bar minimum input pressure for 350 bar fill with 4:1 compression ratio. Lower input possible with reduced fill pressure